



Specifications	D7135	07145	D7150	D7165	D7175
Worktable: mm	600*320	750*420	850*450	1050*600	1050*600
X-Y travel: mm	350*250	450*350	500*400	600*500	700*500
Z axis travel	200	200	200	250	250
Spindle travel	200	200	280	550	550
Elektrode head to worktable	200-450	200-500	200-580	200-850	200-850
Working tank inner size	880*580*360	1100*660*420	1250*790*510	1500*800*500	1500*800*500
Working oil tank size: L	250	400	460	980	980
Max. Electrode weight	so	100	150	250	250
Worktable loading: kgs	500	1000	1500	2500	2800
Machine size	1350*1150*2100	1470*1250*2150	1600*1470*2400	2050*1850*2450	2250*1960*2450
Packing size: CBM	6.5 CBM	8 CBM	9 CBM	15 CBM	17 CBM
Machine weight	1450	1950	2450	3500	4000
Processing Current	30/50 A	30/50/75 A	30/50/75 A	30/50/75 A	30/50/75 A
Max. Erosion efficiency	350/550	350/550/700	350/550/700	350/550/700	350/550/700
Positioning accuracy	0.005	0.005	0.005	0.005	0.005
Repositioning accuracy	0.003	0.003	0.003	0.003	0.003
Max. Roughness	Ra: 0.3	Ra: 0.3	Ra: 0.3	Ra:0.3	Ra: 0.3
Max. Electrode consumption	< 0.2%	< 0.2%	< 0.2%	< 0.2%	< 0.2%
Controller size	750*650*1750	750*650*1750	750*650*1750	750*650*1750	750*650*1750
Controller weight	200kgs	200kgs	200kgs	200kgs	200kgs